



# ENHANCED CROSS DOMAIN SENTIMENTAL CLASSIFICATION USING PATTERN RECOGNITION

**S.Maguda Gowreeswari, Dr. R.Manickachezian**

*Research Scholar, Dr. Mahalingam Centre for Research and Development, NGM College, Pollachi, India*

*Department of Computer Science, N G M College (Autonomous), Pollachi, Coimbatore - 642001, India*

*Email: [gowrisivakrishnan@gmail.com](mailto:gowrisivakrishnan@gmail.com), [chezian\\_r@yahoo.co.in](mailto:chezian_r@yahoo.co.in)*

## ABSTRACT

Millions of users share their opinions on Social Networks, making it a valuable platform for tracking and analyzing public sentiment. Such tracking and analysis can provide critical information for decision making in various domains. Therefore it has attracted attention in both academia and industry. Previous research mainly focused on modelling and tracking public sentiment. In this work, we move one step further to interpret sentiment variations. We observed that emerging topics (named foreground topics) within the sentiment variation periods are highly related to the genuine reasons behind the variations. Proposed work that tries to analyze and interpret the public sentiment variations in micro blogging services. Two novel generative models are developed to solve the reason mining problem. The two proposed models are general: they can be applied to other tasks such as finding topic differences between two sets of documents. We propose a sentimental data analysis model using Neural Networks. Both positive and negative feed backs will be calculated here. These foreground topics can give potential interpretations of the sentiment variations. To further enhance the readability of the mined reasons, we select the most representative tweets for foreground topics and develop another generative model called Reason Candidate and Background LDA (RCB-LDA) to rank them with respect to their popularity within the variation period.

**Keywords:** *Sentiments, Neural network, Decision making, parameter estimation*

## 1. Related Work

Social media sites (e.g., YouTube, and Facebook) are a popular distribution outlet for users looking to share their experiences and interests on the Web. These sites host substantial amounts of user-contributed materials (e.g., photographs, videos, and textual content) for a wide variety of real-world events of different type and scale. By automatically identifying these events and their associated user-contributed social media documents, which is the focus of this paper, we can enable event browsing and search in state-of-the-art search engines.[1].Presents parameter estimation methods common with discrete probability distributions, which is of particular interest in text modelling. Starting with maximum likelihood, a posterior and Bayesian estimation, central concepts like



conjugate distributions and Bayesian networks are reviewed. As an application, the model of latent Dirichlet allocation (LDA) is explained in detail with a full derivation of an approximate inference algorithm based on Gibbs sampling, including a discussion of Dirichlet hyper parameter estimation.[2]. Web advertising (Online advertising), a form of advertising that uses the World Wide Web to attract customers, has become one of the world’s most important marketing channels. This paper addresses the mechanism of Content Oriented advertising (Contextual advertising), which refers to the assignment of relevant ads within the content of a generic web page, e.g. blogs. As blogs become a platform for expressing personal opinion, they naturally contain various kinds of expressions, including both facts and comments of both a positive and negative nature. In this paper, we propose the utilization of sentiment detection to improve Web-based contextual advertising. The proposed SOCA (Sentiment-Oriented Contextual Advertising) framework aims to combine contextual advertising matching with sentiment analysis to select ads that are related to the positive (and neutral) aspects of a blog and rank them according to their relevance [3].

## 2. Existing Model

### 2.1.Mapping Function

The main strategy of mapping the words and documents to the space is to first compute the word embeddings, and then derive the document embeddings based on the word embeddings by considering the word occurrences. Linear projection is assumed to transform the original feature representation of words to their embedding presentation. Specifically, a  $k \times d_A$  projection matrix  $P_A$  is used to map words in domain A to a  $k$ -dimensional embedding space  $\mathbb{R}^k$ , while a  $k \times d_B$  projection matrix  $P_B$  is used to map words in domain B to the same embedding space. Given in total  $M+M_A$  words in domain A including the  $M$  pivots appearing in both domains and  $M_A$  non-pivot words only appearing in domain A, we let  $n \in \mathbb{Z}^{M+M_A}$ .

$I \in \mathbb{O}^{M+M_A}$ .

Denote their corresponding word embeddings stored in an  $(M+M_A) \times k$  embedding matrix  $e \in \mathbb{Z}^{(M+M_A) \times k}$  computed by the linear projection mapping given as

$$\tilde{Z}_A^T = \left[ P_A^T U_A^T, P_A^T A^T \right].$$

Similarly,  $n \in \mathbb{Z}^{(M+M_B)}$  denotes the embeddings forward  $s$  in domain B, which results in an  $(M+M_B) \times k$  embedding matrix  $e \in \mathbb{Z}^{(M+M_B) \times k}$  computed by

$$\tilde{Z}_B^T = \left[ P_B^T U_B^T, P_B^T B^T \right].$$



### 3. Proposed Methodology

All the problems and requirements were overcome in the proposed architecture, through developing a dedicated application for this analysis model. This application will make a major impact among the market researchers like data analyst, data reporter, business analyst, business growth predictors and etc. This application is easy, simple and user friendly to use all types of sentimental analysis model. Here raw data will be given as the input and out the output will a tremendous data reporting model. Some marketers prefer leaving the analysis to dedicated methods, the methods behind sentiment analysis is nothing short from fascinating the various levels of analysis, the detail and the intricacy that make this analysis more accurate when performed by another human rather than a machine. Nowadays, sentiment analysis is an integral part of social listening, although it can also be performed on its own. Sentiment analysis is more than just a feature in a social analytics method. This is a field that is still being studied. While this comment is general, it can be broken down into sentences. This comment has a number of opinions around Simply Measured, both positive and negative. Sentiment refers to the emotion behind a social media mention. It's a way to measure the tone of the conversation is the person happy, annoyed, and angry or neutrals. Sentiment adds important context to social conversations. Without it, measurement of mentions alone could be misleading. If the requirement is to measuring mentions for a company's new product, user might assume a surge in mentions meant it was being well received. After all, more mentions more people talking about the product. Measuring sentiment will help you understand the overall feeling surrounding a particular subject, enabling you to create a broader and more complete picture of the social conversations that matter to you.

### 4. Algorithm

#### 4.1.Declaration

DS = data set

V = Vocabulary (Extracted from dataset)

C = Categorization :sen count

N = Occurrence

$A(P_j | N_i)$  = Array Deceleration:  $P_j$  denotes positive and  $N_i$  denoted negative

R = Result

1. Let initiate the process : class index : System.Web.UI.Page, Open database access to receive the dataset: OleDbConnection con;
2. Declare Array : ArrayList recomment = new ArrayList(); Received data will be stored in an array;



3. `String.IsNullOrEmpty (GridView1.Rows[i].Cells[j].ToString())` Confirming the data grid is empty to receive the data;
4. Now LET dataset will be DS;
5. Updating positive word : `posi.Add((string)red[0].ToString());` Positive word will be stored as the separate string collection : `cmd1.ExecuteReader();`
6. Updating Negative word : `nega.Add((string)red[0].ToString());` Negative word will be stored as the separate string collection : `cmd2.ExecuteReader();`
7. Grid updating: `GridView2.Rows[i].Cells[j].Text == posi` and `nega`;
8. Merging as a neural Networks =  $A(P_j | N_i)$  array deceleration for  $P_j$  and  $N_i$ ;
9. `OleDbDataReader rd1 = cmd1.ExecuteReader();`
10. `postedby = rd[0].ToString();`

```
pdate = rd[1].ToString();
```

```
ptime = rd[2].ToString();
```

```
shareto = rd[3].ToString();
```

```
post = rd[4].ToString();
```

```
memname = rd[5].ToString();
```

```
comment = rd[6].ToString();
```

```
memdate = rd[7].ToString();
```

11. Display the DS grid value in the data reader : `GridView4.Visible = false; cmd1 = new OleDbCommand(query, con);`
12. Data analysis process: Let  $V =$  Vocabulary: `toterr.Add(rd1[0].ToString());` Splitting word as vocabulary
13. Also Split word will be stored as the  $C =$  Categorization : `string[] a = toterr [i1] .ToString () .ToUpper().Split(' ');`
14. Now Analysis will produce the result: Compare  $Srting[DS,V,C]$  with  $A(P_j | N_i)$
15. `loadarr();`

```
pcount = posi.Count;
```

```
ncount = nega.Count;
```

```
scount = sen.Count;
```

16. `(sen[i].ToString() == posi[j].ToString());`
17. `(sen[i].ToString() == nega[j].ToString());`



18. Display Result R : input sen = r count
19. rcount = rank.Count; for ranking: (sen[i].ToString() == rank[j].ToString())  
  
stat = rd[8].ToString();
20. Display ranking result : string[] a = toterr[i1].ToString().ToUpper().Split(' ');
21. Retrieve data from the DB
22. Display results in charts

### 5. Result And Discussion

This chapter deals with all the result and the obtain values from the available dataset. According to this thesis, initially all the data will be considered as the input data and processing data. But as per proposed method we need to preprocess the data for a fine tuned result.

<b>Total Number of Data</b>	<b>199</b>
<b>Number of Positive Data</b>	<b>100</b>
<b>Number of Negative Data</b>	<b>39</b>
<b>Number of Moderate Data</b>	<b>60</b>





Fig 1.1

Total data	199
Number of positive data	100
Number of negative data	39
Number of moderate data	60


Fig1.2




**Performance Chart**




**Timing Chart**



**Data Chart**



**Redundant Chart**



## 6. Conclusion

Classification is very essential to organise data, retrieve information correctly and swiftly. Implementing machine learning to classify data is not easy given the huge amount of heterogeneous data that's present in the web. Text categorization algorithm depends entirely on the accuracy of the training data set for building its decision trees. The text categorization algorithm learns by supervision. It has to be shown what instances have what results. Due to this text categorization algorithm, it cannot be successfully classify documents in the web.



The data in the web is unpredictable, volatile and most of it lacks Meta data. The way forward for information retrieval in the web, in the future opinion would be to advocate the creation of a semantic web where algorithms which are unsupervised and reinforcement learners are used to classify and retrieve data. Thus the thesis explains the trends, threads and process of the text categorization algorithm which was implemented for finding the sensitive data analysis

## References

- [1] Learning similarity metrics for event identification in social media. H. Becker, M. Naaman, and L. Gravano, , 2010“Learning similarity metrics for event identification in social media,” in Proc. 3rd ACM WSDM, Macau, China.
- [2] Parameter estimation for text analysis. G. Heinrich, 2009, “Parameter estimation for text analysis,” Fraunhofer IGD, Darmstadt, Germany, Univ. Leipzig, Leipzig, Germany, Tech. Rep.
- [3] J. Bollen, H. Mao, and X. Zeng, Mar. 2011 “Twitter mood predicts the stock market,”*J. Comput. Sci.*, vol. 2, no. 1, pp. 1–8.
- [4] D. Chakrabarti and K. Punera, 2011,“Event summarization using tweets,” in Proc. 5th Int. AAAI Conf. Weblogs Social Media, Barcelona, Spain.
- [5] A. Go, R. Bhayani, and L. Huang, 2009 “Twitter sentiment classification using distant supervision,” CS224N Project Rep., Stanford: 1–12.
- [6] T. L. Griffiths and M. Steyvers, Apr. 2004, “Finding scientific topics,” inProc. Nat. Acad. Sci. USA, vol. 101, (Suppl. 1), pp. 5228–5235.
- [7] D. Hall, D. Jurafsky, and C. D. Manning, 2008, “Studying the history of ideas using topic models,” inProc. Conf. EMNLP, Stroudsburg, PA, USA, pp. 363–371.
- [8] G. Heinrich, 2009, “Parameter estimation for text analysis,” Fraunhofer IGD, Darmstadt, Germany, Univ. Leipzig, Leipzig, Germany, Tech. Rep.
- [19] Z. Hong, X. Mei, and D. Tao, 2012, “Dual-force metric learning for robust distracter-resistant tracker,” in Proc. ECCV, Florence, Italy.
- [10] M. Hu and B. Liu, 2004, “Mining and summarizing customer reviews,” in Proc. 10th ACM SIGKDD, Washington, DC, USA.
- [11] Y. Hu, A. John, F. Wang, and D. D. Seligmann, 2012, “Et-Ida: Joint topic modeling for aligning events and their twitter feedback,” inProc. 26th AAAI Conf. Artif. Intell., Vancouver, BC, Canada.
- [12] L. Jiang, M. Yu, M. Zhou, X. Liu, and T. Zhao, 2011, “Target-dependent twitter sentiment classification,” in Proc. 49th HLT, Portland, OR, USA.
- [13] J. Leskovec, L. Backstrom, and J. Kleinberg, 2009, “Meme-tracking and the dynamics of the news cycle,” in Proc. 15th ACM SIGKDD, Paris, France.
- [14] C. X. Lin, B. Zhao, Q. Mei, and J. Han, 2010, “Pet: A statistical model for popular events tracking in social communities,” in Proc. 16<sup>th</sup> ACM SIGKDD, Washington, DC, USA.
- [15] F. Liu, Y. Liu, and F. Weng, 2011, “Why is “SXSW” trending? Exploring multiple text sources for twitter topic summarization,” inProc. Workshop LSM, Portland, OR, USA.



## **BIOGRAPHY**



**S.Maguda Gowreeswari** received her BCA (Computer Application) from NGM College, Pollachi, India. She completed her Master of Computer Application (MCA) from NGM College, Pollachi, India. Currently, she is a Research Scholar at Department of Computer Science, NGM College, Pollachi, India. She participated in a International Conference. Her area of interest includes Data mining, Sentimental analysis.



**Dr.R.ManickaChezian** received his M.Sc., degree in Applied Science from P.S.G College of Technology, Coimbatore, India in 1987. He completed his M.S. degree in Software Systems from Birla Institute of Technology and Science, Pilani, Rajasthan, India and Ph.D degree in Computer Science from School of Computer Science and Engineering, Bharathiar University, Coimbatore, India. He served as a Faculty of Maths and Computer Applications at P.S.G College of Technology, Coimbatore from 1987 to 1989. Presently, he has been working as an Associate Professor of Computer Science in N G M College (Autonomous), Pollachi under Bharathiar University, Coimbatore, India since 1989. He has published one-fifty papers in international/national journal and conferences: He is a recipient of many awards like DeshaMithra Award and Best Paper Award. Recently he received the award “Best Computer Science Faculty of the Year 2015” from Association of Scientists, Developers and Faculties. His research focuses on Network Databases, Data Mining, Distributed Computing, Data Compression, Mobile Computing, Real Time Systems and Bio-Informatics.